

Docker

Quelle: <https://docs.docker.com/engine/install/debian/#install-using-the-repository>

```
# Add Docker's official GPG key:
apt update
apt install ca-certificates curl
install -m 0755 -d /etc/apt/keyrings
curl -fsSL https://download.docker.com/linux/debian/gpg -o
/etc/apt/keyrings/docker.asc
chmod a+r /etc/apt/keyrings/docker.asc

# Add the repository to Apt sources:
echo \
  "deb [arch=$(dpkg --print-architecture) signed-
  by=/etc/apt/keyrings/docker.asc] https://download.docker.com/linux/debian \
  $(. /etc/os-release && echo "$VERSION_CODENAME") stable" | \
  tee /etc/apt/sources.list.d/docker.list > /dev/null
apt update
apt install docker-ce docker-ce-cli containerd.io docker-buildx-plugin
docker-compose-plugin
```

Migrate seafile

Quelle: https://manual.seafile.com/docker/non_docker_to_docker/

```
## Connect do DB server
mysql -u root -p
```

```
## Note, CHANGE the password according TO the actual password you USE
GRANT ALL PRIVILEGES ON *.* TO 'seafile'@'%' IDENTIFIED BY 'your-password'
WITH GRANT OPTION;
```

```
## GRANT seafile USER can CONNECT the DATABASE FROM any IP address
GRANT ALL PRIVILEGES ON `seafile_ccnet_db`.* TO 'seafile'@'%';
GRANT ALL PRIVILEGES ON `seafile_seafile_db`.* TO 'seafile'@'%';
GRANT ALL PRIVILEGES ON `seafile_seahub_db`.* TO 'seafile'@'%';
```

```
## Restart MySQL
systemctl restart mariadb
```

From:

<https://host.docker.internal:552/> - **Meine kleine Dokumentation**

Permanent link:

<https://host.docker.internal:552/doku.php?id=docker&rev=1728330066>

Last update: **2024/10/07 19:41**

