

Kimai Open Source Time Tracking

```
CREATE USER 'kimai'@'localhost' IDENTIFIED BY 'PASSWORD1';
CREATE DATABASE `kimai`;
GRANT ALL privileges ON `kimai`.* TO 'kimai'@'localhost';
flush privileges;
```

```
mkdir -p /var/www/html/meinekleinefarm.net/kimai
cd /var/www/html/meinekleinefarm.net/kimai
wget https://github.com/kimai/kimai/releases/download/1.1.0/kimai_1.1.0.zip
unzip kimai_1.1.0.zip
rm kimai_1.1.0.zip
```

```
<VirtualHost *:80>
    ServerName piwik.meinekleinefarm.net
    Redirect permanent / https://piwik.meinekleinefarm.net/
</VirtualHost>

<IfModule mod_ssl.c>
    <VirtualHost *:443>
        ServerAdmin webmaster@meinekleinefarm.net
        ServerName kimai.meinekleinefarm.net
        ServerAlias kimai.meinekleinefarm.net

        DocumentRoot /var/www/html/meinekleinefarm.net/kimai/

        <Directory /var/www/html/meinekleinefarm.net/kimai/>
            AllowOverride All
        </Directory>

        ErrorLog ${APACHE_LOG_DIR}/error.log
        CustomLog ${APACHE_LOG_DIR}/access.log combined

        SSLEngine on
        SSLCertificateFile
/etc/letsencrypt/live/meinekleinefarm.net/fullchain.pem
        SSLCertificateKeyFile
/etc/letsencrypt/live/meinekleinefarm.net/privkey.pem

        <FilesMatch "\.(cgi|shtml|phtml|php)$">
            SSLOptions +StdEnvVars
        </FilesMatch>
        <Directory /usr/lib/cgi-bin>
            SSLOptions +StdEnvVars
        </Directory>

        BrowserMatch "MSIE [2-6]" \
            nokeepalive ssl-unclean-shutdown \
```

downgrade-1.0 force-response-1.0

```
BrowserMatch "MSIE [17-9]" ssl-unclean-shutdown
</VirtualHost>
</IfModule>
```

```
a2ensite kimai.meinekleinefarm.net.conf
service apache2 reload
```

From:

<https://host.docker.internal:552/> - **Meine kleine Dokumentation**

Permanent link:

<https://host.docker.internal:552/doku.php?id=kimai&rev=1490269111>

Last update: **2017/03/23 11:38**

