Linux Dash

Quellen:

- https://linux-dash.github.io/
- https://httpd.apache.org/docs/current/howto/auth.html

```
mkdir -p /var/www/html/meinekleinefarm.net/dash/

git clone --depth 1 https://github.com/linux-dash/linux-dash.git
/var/www/html/meinekleinefarm.net/dash/
```

*

```
Cloning into 'dash'...
remote: Counting objects: 78, done.
remote: Compressing objects: 100% (71/71), done.
remote: Total 78 (delta 5), reused 48 (delta 3), pack-reused 0
Unpacking objects: 100% (78/78), done.
Checking connectivity... done.
```

```
chown www-data:www-data -R /var/www/html/

htpasswd -B -c /etc/apache2/.htpasswd demo-user
New password:
Re-type new password:
Adding password for user demo-user

htpasswd -B /etc/apache2/.htpasswd demo-user2
New password:
Re-type new password:
Adding password for user demo-user2

nano /etc/apache2/sites-available/dash.meinekleinefarm.net.conf
```

dash.meinekleinefarm.net.conf

```
<VirtualHost *:80>
        ServerName dash.meinekleinefarm.net
        Redirect permanent / https://dash.meinekleinefarm.net/
</VirtualHost>

<IfModule mod_ssl.c>
        <VirtualHost *:443>
                ServerAdmin webmaster@meinekleinefarm.net
                ServerName dash.meinekleinefarm.net
                ServerAlias dash.meinekleinefarm.net
```

```
                DocumentRoot
/var/www/html/meinekleinefarm.net/dash/app/

                <Directory /var/www/html/meinekleinefarm.net/dash/app/>
                        AuthType Basic
                        AuthName "Linux Dash 2.0"
                        AuthUserFile /etc/apache2/.htpasswd
                        Require valid-user

                        AllowOverride All
                </Directory>

                ErrorLog ${APACHE_LOG_DIR}/error.log
                CustomLog ${APACHE_LOG_DIR}/access.log combined

                SSLEngine on
                SSLCertificateFile
/etc/letsencrypt/live/meinekleinefarm.net/fullchain.pem
                SSLCertificateKeyFile
/etc/letsencrypt/live/meinekleinefarm.net/privkey.pem

                <FilesMatch "\.(cgi|shtml|phtml|php)$">
                                SSLOptions +StdEnvVars
                </FilesMatch>
                <Directory /usr/lib/cgi-bin>
                                SSLOptions +StdEnvVars
                </Directory>

                BrowserMatch "MSIE [2-6]" \
                                nokeepalive ssl-unclean-shutdown \
                                downgrade-1.0 force-response-1.0
                BrowserMatch "MSIE [17-9]" ssl-unclean-shutdown
        </VirtualHost>
</IfModule>
```

```
a2ensite dash.meinekleinefarm.net.conf
service apache2 reload
```

From:
https://dokuwiki.meinekleinefarm.net/ - **Meine kleine Dokumentation**

Permanent link:
https://dokuwiki.meinekleinefarm.net/doku.php?id=linux_dash&rev=1478721264

Last update: **2016/11/09 19:54**