Roundcube

wget
https://github.com/roundcube/roundcubemail/releases/download/1.2.2/roundcube
mail-1.2.2-complete.tar.gz
tar -xzvf roundcubemail-1.2.2-complete.tar.gz
mv roundcubemail-1.2.2 /var/www/html/meinekleinefarm.net/roundcube
chown www-data:www-data -R /var/www/html/
nano /etc/apache2/sites-available/mail.meinekleinefarm.net.conf

mail.meinekleinefarm.net.conf

```
<VirtualHost *:80>
        ServerName mail.meinekleinefarm.net
        Redirect permanent / https://mail.meinekleinefarm.net/
</VirtualHost>

<IfModule mod_ssl.c>
        <VirtualHost *:443>
                ServerAdmin webmaster@meinekleinefarm.net
                ServerName mail.meinekleinefarm.net
                ServerAlias mail.meinekleinefarm.net

                DocumentRoot
/var/www/html/meinekleinefarm.net/roundcube/

                <Directory
/var/www/html/meinekleinefarm.net/roundcube/>
                        AllowOverride All
                </Directory>

                ErrorLog ${APACHE_LOG_DIR}/error.log
                CustomLog ${APACHE_LOG_DIR}/access.log combined

                SSLEngine on
                SSLCertificateFile
/etc/letsencrypt/live/meinekleinefarm.net/fullchain.pem
                SSLCertificateKeyFile
/etc/letsencrypt/live/meinekleinefarm.net/privkey.pem

                <FilesMatch "\.(cgi|shtml|phtml|php)$">
                        SSLOptions +StdEnvVars
                </FilesMatch>
                <Directory /usr/lib/cgi-bin>
                        SSLOptions +StdEnvVars
                </Directory>

                BrowserMatch "MSIE [2-6]" \
```

```
                                nokeepalive ssl-unclean-shutdown \
                                downgrade-1.0 force-response-1.0
                BrowserMatch "MSIE [17-9]" ssl-unclean-shutdown
        </VirtualHost>
    </IfModule>
```

```
a2ensite mail.meinekleinefarm.net.conf
service apache2 reload
mysql -u root -p
```

```sql
CREATE USER 'roundcubemail'@'localhost' IDENTIFIED BY 'PASSW0RD1';
CREATE DATABASE `roundcubemail`;
GRANT ALL privileges ON `roundcubemail`.* TO 'roundcubemail'@'localhost';
flush privileges;
```

<code bash>

From:
https://host.docker.internal:552/ - **Meine kleine Dokumentation**

Permanent link:
https://host.docker.internal:552/doku.php?id=roundcube&rev=1479937906

Last update: **2016/11/23 21:51**