

## Quelle:

1. [https://manual.seafiler.com/maintain/backup\\_recovery.html](https://manual.seafiler.com/maintain/backup_recovery.html)
2. <https://unwahrscheinlichkeitsdrive.de/2015/02/07/seafiler-migration/>

Auf dem „alten“ Server:

```
<<Alle seafiler Dienste stoppen>>
mysqldump -h localhost -u root -p seafiler_ccnet-db > ccnet-db.sql
mysqldump -h localhost -u root -p seafiler_seafiler-db > seafiler-db.sql
mysqldump -h localhost -u root -p seafiler_seahub-db > seahub-db.sql
scp -r -P 22 /root/seafiler_db/ccnet-db.sql root@192.168.1.2:/root
scp -r -P 22 /root/seafiler_db/seafiler-db.sql root@192.168.1.2:/root
scp -r -P 22 /root/seafiler_db/seahub-db.sql root@192.168.1.2:/root
cd /home/seafiler/seafiler-server
tar -czvf - * | ssh -p 22 root@192.168.1.2 'tar -xhvf - -C /opt/seafiler/'
```

Auf dem „neuen“ Server:

```
apt install python2.7 libpython2.7 python-setuptools python-imaging \
python-ldap python-mysqldb python-memcache python-urllib3 \
memcached python-memcache -y
adduser --disabled-login --home /opt/seafiler --shell /bin/false --gecos
"Seafiler" seafiler
chown seafiler:root /opt/seafiler -R
mysql -u root -p
```

```
CREATE USER 'seafiler'@'localhost' IDENTIFIED BY 'PASSWORD1';
CREATE DATABASE `seafiler_ccnet-db`;
CREATE DATABASE `seafiler_seafiler-db`;
CREATE DATABASE `seafiler_seahub-db`;
```

```
mysql -u root -p seafiler_ccnet-db < /root/ccnet-db.sql
mysql -u root -p seafiler_seafiler-db < /root/seafiler-db.sql
mysql -u root -p seafiler_seahub-db < /root/seahub-db.sql
mysql -u root -p
```

```
GRANT ALL privileges ON `seafiler_ccnet-db`.* TO 'seafiler'@'localhost';
GRANT ALL privileges ON `seafiler_seafiler-db`.* TO 'seafiler'@'localhost';
GRANT ALL privileges ON `seafiler_seahub-db`.* TO 'seafiler'@'localhost';
flush privileges;
```

```
nano /opt/seafiler/conf/ccnet.conf
nano /opt/seafiler/conf/seafiler.conf
nano /opt/seafiler/conf/seahub_settings.py
nano /opt/seafiler/ccnet/seafiler.ini
su seafiler
cd /opt/seafiler/seafiler-server-latest/
./seaf-fsck.sh
./seafiler.sh start
./seahub.sh start-fastcgi
```

```
exit
```

```
mkdir /var/www/html/meinekleinefarm.net/seafile  
nano /etc/apache2/sites-available/files.meinekleinefarm.net.conf
```

[files.meinekleinefarm.net.conf](#)

```
<VirtualHost *:443>  
    ServerAdmin webmaster@meinekleinefarm.net  
    ServerName files.meinekleinefarm.net  
    ServerAlias files.meinekleinefarm.net  
  
    DocumentRoot /var/www/html/meinekleinefarm.net/seafile  
  
    SSLEngine On  
    SSLCertificateFile /opt/seafile/certificates/cacert.pem  
    SSLCertificateKeyFile /opt/seafile/certificates/privkey.pem  
    SSLCertificateChainFile  
/opt/seafile/certificates/sub.class1.server.ca.pem  
  
    Alias /media /opt/seafile/seafile-server-latest/seahub/media  
  
    <Location /media>  
        ProxyPass !  
        Require all granted  
    </Location>  
  
    RewriteEngine On  
  
    #  
    # seafile fileserver  
    #  
    ProxyPass /seafhttp http://127.0.0.1:8082  
    ProxyPassReverse /seafhttp http://127.0.0.1:8082  
    RewriteRule ^/seafhttp - [QSA,L]  
  
    #  
    # seahub  
    #  
    SetEnvIf Request_URI . proxy-fcgi-pathinfo=unescape  
    SetEnvIf Authorization "(.*)" HTTP_AUTHORIZATION=$1  
    ProxyPass / fcgi://127.0.0.1:8000/  
</VirtualHost>
```

```
a2ensite files.meinekleinefarm.net.conf  
service apache2 reload
```

From:

<https://host.docker.internal:552/> - **Meine kleine Dokumentation**

Permanent link:

[https://host.docker.internal:552/doku.php?id=seafire\\_server\\_migration&rev=1475873310](https://host.docker.internal:552/doku.php?id=seafire_server_migration&rev=1475873310)

Last update: **2016/10/07 20:48**

