Unattended Upgrades

Quelle

- https://wiki.debian.org/UnattendedUpgrades

```
apt update
nano /etc/aliases
```

Add the following line:

```
root:   hostmaster@domain.de
```

newaliases apt install postfix -y </code>

- ```
  > Satellite system
  > FQDN
  > SMTP relay host
  ```

```
apt install unattended-upgrades -y
dpkg-reconfigure -plow unattended-upgrades
<<Yes>>
nano /etc/apt/apt.conf.d/50unattended-upgrades
```

Uncomment →

```
Unattended-Upgrade::Mail "root";
```

Optional, postifx testen:

```
apt install mailutils -y
mail root
```

- ```
  Cc:
  Subject: Test
  Hallo!
  Ctrl+D
  tail -f /var/log/mail.log
  ```

```
Oct 11 17:39:56 debian postfix/smtp[31370]: 8594940A46:
to=<hostmaster@domain.de>, orig_to=<root@debian.domain.local>,
relay=smtp.domain.de[1.2.3.4]:25, delay=0.14, delays=0/0/0.11/0.03,
dsn=2.0.0, status=sent (250 2.0.0 Ok: queued as B19BF48C21)
```

From:
https://host.docker.internal:552/ - **Meine kleine Dokumentation**

Permanent link:
https://host.docker.internal:552/doku.php?id=unattended-upgrades&rev=1478644926

Last update: **2016/11/08 22:42**