

Dovecot



Baustelle / Work in Progress

Setup

```
apt install -t jessie-backports dovecot-core dovecot-imapd dovecot-lmtpd -y  
cp -arf /etc/dovecot/conf.d/ /etc/dovecot/conf.d.BAK
```

```
cd /etc/dovecot/conf.d  
nano 10-mail.conf
```

- `mail_location = maildir:/var/mail/vhosts/%d/%n`

```
mkdir -p /var/mail/vhosts/meinekleinefarm.net  
mkdir -p /var/mail/vhosts/mgs-ullrich.de
```

```
#groupadd -g 5000 vmail  
#useradd -r -g vmail -u 5000 vmail -d /var/mail/vhosts -c "Dovecot virtual  
mail user"  
#chown -R vmail:vmail /var/mail/vhosts/  
chown -R mail:mail /var/mail/vhosts/
```

```
nano 10-master.conf
```

- ```
service imap-login {
 inet_listener imap {
 #port = 143
 }
 inet_listener imaps {
 port = 993
 ssl = yes
 }

 service lmtp {
 unix_listener /var/spool/postfix/private/dovecot-lmtp {
 group = postfix
 user = postfix
 mode = 0666
 }
 }
}
```

```
service auth {
 # Postfix smtp-auth
 unix_listener /var/spool/postfix/private/auth {
 mode = 0666
 user = postfix
 group = postfix
 }
}
```

## **nano** 10-auth.conf

```
• disable_plaintext_auth = yes
Today however many people use SSL/TLS, and there's no problem with
sending unencrypted password inside SSL secured connections.
auth_mechanisms = plain login

#!include auth-system.conf.ext
#!include auth-sql.conf.ext
#!include auth-ldap.conf.ext
!include auth-passwdfile.conf.ext
#!include auth-checkpassword.conf.ext
#!include auth-vpopmail.conf.ext
#!include auth-static.conf.ext
```

## **nano** auth-passwdfile.conf.ext

```
• # Authentication for passwd-file users. Included from 10-auth.conf.

passwd-like file with specified location.
<doc/wiki/AuthDatabase.PasswdFile.txt>

passdb {
 driver = passwd-file
 args = scheme=SHA512-CRYPT username_format=%u /etc/dovecot/dovecot-
users
}

userdb {
 driver = static
 args = uid=mail gid=mail home=/var/mail/vhosts/%d/%n
}
```

## Dovecot Users PasswdFile

```
doveadm pw -l
doveadm pw -s SHA512-CRYPT
nano ../dovecot-users
```

- #meinekleinefarm.net  
xenadmin@meinekleinefarm.net:{SHA512-CRYPT}\$6\$XYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyz
- #mgs-ullrich.de  
example@mgs-ullrich.de:{SHA512-CRYPT}\$6\$XYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyz

## 10-ssl.conf

```
nano 10-ssl.conf
```

- ssl = required  
ssl\_cert = </etc/letsencrypt/live/meinekleinefarm.net/fullchain.pem  
ssl\_key = </etc/letsencrypt/live/meinekleinefarm.net/privkey.pem

## 10-logging.conf

```
nano 10-logging.conf
```

- log\_path = /var/log/dovecot.log

## Setup logrotate

```
nano /etc/logrotate.d/dovecot
```

- /var/log/dovecot\*.log {  
missingok  
notifempty  
delaycompress  
sharedscripts  
postrotate

```
doveadm log reopen
endscript
}
```

**Fin**

```
systemctl restart dovecot
```

From:

<https://dokuwiki.meinekleinefarm.net/> - **Meine kleine Dokumentation**

Permanent link:

[https://dokuwiki.meinekleinefarm.net/doku.php?id=dovecot\\_installation&rev=1478725105](https://dokuwiki.meinekleinefarm.net/doku.php?id=dovecot_installation&rev=1478725105)

Last update: **2016/11/09 20:58**

