

Dovecot



Baustelle / Work in Progress

Setup

```
apt install -t jessie-backports dovecot-core dovecot-imapd dovecot-lmtpd -y  
cp -arf /etc/dovecot/conf.d/ /etc/dovecot/conf.d.BAK
```

```
cd /etc/dovecot/conf.d  
nano 10-mail.conf
```

- mail_location = maildir:/var/mail/vhosts/%d/%n

```
mkdir -p /var/mail/vhosts/meinekleinefarm.net  
mkdir -p /var/mail/vhosts/mgs-ullrich.de
```

```
groupadd -g 5000 vmail  
useradd -r -g vmail -u 5000 vmail -d /var/mail/vhosts -c "Dovecot virtual  
mail user"  
chown -R vmail:vmail /var/mail/vhosts/  
  
nano 10-master.conf
```

- service imap-login {
 inet_listener imap {
 #port = 143
 }
 inet_listener imaps {
 port = 993
 ssl = yes
 }

 service lmtp {
 unix_listener /var/spool/postfix/private/dovecot-lmtp {
 group = postfix
 user = postfix
 mode = 0666
 }
 }
}

```
service auth {  
    # Postfix smtp-auth  
    unix_listener /var/spool/postfix/private/auth {  
        mode = 0666  
        user = postfix  
        group = postfix  
    }  
}
```

nano 10-auth.conf

- `disable_plaintext_auth = yes`
Today however many people use SSL/TLS, and there's no problem with sending unencrypted password inside SSL secured connections.
`auth_mechanisms = plain login`

#!include auth-system.conf.ext
#!include auth-sql.conf.ext
#!include auth-ldap.conf.ext
!include auth-passwdfile.conf.ext
#!include auth-checkpassword.conf.ext
#!include auth-vpopmail.conf.ext
#!include auth-static.conf.ext

nano auth-passwdfile.conf.ext

- # Authentication for passwd-file users. Included from 10-auth.conf.

passwd-like file with specified location.
<doc/wiki/AuthDatabase.PasswdFile.txt>

`passdb {
 driver = passwd-file
 args = scheme=SHA512-CRYPT username_format=%u /etc/dovecot/dovecot-users
}`

`userdb {
 driver = static
 args = uid=vmail gid=vmail home=/var/mail/vhosts/%d/%n
}`

Dovecot Users PasswdFile

```
doveadm pw -l  
doveadm pw -s SHA512-CRYPT  
nano ../dovecot-users
```

- #meinekleinefarm.net
xenadmin@meinekleinefarm.net:{SHA512-CRYPT}\$6\$XYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyz
- #mgs-ullrich.de
example@mgs-ullrich.de:{SHA512-CRYPT}\$6\$XYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyz

10-ssl.conf

```
nano 10-ssl.conf
```

- ssl = required
ssl_cert = </etc/letsencrypt/live/meinekleinefarm.net/fullchain.pem
ssl_key = </etc/letsencrypt/live/meinekleinefarm.net/privkey.pem

10-logging.conf

```
nano 10-logging.conf
```

- log_path = /var/log/dovecot.log

Setup logrotate

```
nano /etc/logrotate.d/dovecot
```

- /var/log/dovecot*.log {
missingok
notifempty
delaycompress
sharedscripts
postrotate

```
doveadm log reopen  
endscript  
}
```

Fin

```
systemctl restart dovecot
```

From:

<https://dokuwiki.meinekleinefarm.net/> - **Meine kleine Dokumentation**

Permanent link:

https://dokuwiki.meinekleinefarm.net/doku.php?id=dovecot_installation&rev=1478725374

Last update: **2016/11/09 21:02**

