

Dovecot



Baustelle / Work in Progress

Setup

```
apt install -t jessie-backports dovecot-core dovecot-imapd dovecot-lmtpd -y
cp -arf /etc/dovecot/conf.d/ /etc/dovecot/conf.d.BAK
cd /etc/dovecot/conf.d

mkdir -p /var/mail/vhosts/meinekleinefarm.net
mkdir -p /var/mail/vhosts/mgs-ullrich.de
groupadd -g 5000 vmail
useradd -r -g vmail -u 5000 vmail -d /var/mail/vhosts -c "Dovecot virtual mail user"
chown -R vmail:vmail /var/mail/vhosts/
```

10-mail.conf

```
nano 10-mail.conf
```

- mail_location = maildir:/var/mail/vhosts/%d/%n

10-master.conf

```
nano 10-master.conf
```

- service imap-login {
 inet_listener imap {
 #port = 143
 }
 inet_listener imaps {
 port = 993
 ssl = yes
 }

 service lmtp {
 unix_listener /var/spool/postfix/private/dovecot-lmtp {
 group = postfix
 }
 }
}

```
    user = postfix
    mode = 0666
}

service auth {
    # Postfix smtp-auth
    unix_listener /var/spool/postfix/private/auth {
        mode = 0666
        user = postfix
        group = postfix
    }
}
```

10-auth.conf

nano 10-auth.conf

```
• disable_plaintext_auth = yes
  # Today however many people use SSL/TLS, and there's no problem with
  # sending unencrypted password inside SSL secured connections.
  auth_mechanisms = plain login

#!include auth-system.conf.ext
#!include auth-sql.conf.ext
#!include auth-ldap.conf.ext
!include auth-passwdfile.conf.ext
#!include auth-checkpassword.conf.ext
#!include auth-vpopmail.conf.ext
#!include auth-static.conf.ext
```

auth-passwdfile.conf.ext

nano auth-passwdfile.conf.ext

```
• # Authentication for passwd-file users. Included from 10-auth.conf.
  #
  # passwd-like file with specified location.
  # <doc/wiki/AuthDatabase.PasswdFile.txt>

passdb {
    driver = passwd-file
    args = scheme=SHA512-CRYPT username_format=%u /etc/dovecot/dovecot-
users
}
```

```
userdb {  
    driver = static  
    args = uid=vmail gid=vmail home=/var/mail/vhosts/%d/%n  
}
```

Dovecot Users PasswdFile

```
doveadm pw -l  
doveadm pw -s SHA512-CRYPT  
nano ../dovecot-users
```

- #meinekleinefarm.net
xenadmin@meinekleinefarm.net:{SHA512-CRYPT}\$6\$XYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyz
- #mgs-ullrich.de
example@mgs-ullrich.de:{SHA512-CRYPT}\$6\$XYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyz

10-ssl.conf

```
nano 10-ssl.conf
```

- ssl = required
ssl_cert = </etc/letsencrypt/live/meinekleinefarm.net/fullchain.pem
ssl_key = </etc/letsencrypt/live/meinekleinefarm.net/privkey.pem

10-logging.conf

```
nano 10-logging.conf
```

- log_path = /var/log/dovecot.log

Setup logrotate

```
nano /etc/logrotate.d/dovecot
```

```
• /var/log/dovecot*.log {  
    missingok  
    notifempty  
    delaycompress  
    sharedscripts  
    postrotate  
        doveadm log reopen  
    endscript  
}
```

Fin

```
systemctl restart dovecot
```

From:

<https://dokuwiki.meinekleinefarm.net/> - **Meine kleine Dokumentation**

Permanent link:

https://dokuwiki.meinekleinefarm.net/doku.php?id=dovecot_installation&rev=1478725715

Last update: **2016/11/09 21:08**

