

Dovecot



Baustelle / Work in Progress

Quelle

- <http://www.binarytides.com/install-postfix-dovecot-debian/>

Setup

```
apt install -t jessie-backports dovecot-core dovecot-imapd dovecot-lmtpd -y
cp -arf /etc/dovecot/conf.d/ /etc/dovecot/conf.d.BAK
cd /etc/dovecot/conf.d

mkdir -p /var/mail/vhosts/meinekleinefarm.net
mkdir -p /var/mail/vhosts/mgs-ullrich.de
groupadd -g 5000 vmail
useradd -r -g vmail -u 5000 vmail -d /var/mail/vhosts -c "Dovecot virtual mail user"
chown -R vmail:vmail /var/mail/vhosts/
```

10-mail.conf

```
nano 10-mail.conf
```

- `mail_location = maildir:/var/mail/vhosts/%d/%n`

10-master.conf

```
nano 10-master.conf
```

- ```
service imap-login {
 inet_listener imap {
 #port = 143
 }
 inet_listener imaps {
 port = 993
 ssl = yes
 }
}
```

```
}

service lmtp {
 unix_listener /var/spool/postfix/private/dovecot-lmtp {
 group = postfix
 user = postfix
 mode = 0666
 }

service auth {
 # Postfix smtp-auth
 unix_listener /var/spool/postfix/private/auth {
 mode = 0666
 user = postfix
 group = postfix
 }
}
```

## 10-auth.conf

**nano** 10-auth.conf

- disable\_plaintext\_auth = yes  
# Today however many people use SSL/TLS, and there's no problem with sending unencrypted password inside SSL secured connections.  
auth\_mechanisms = plain login  
  
#!include auth-system.conf.ext  
#!include auth-sql.conf.ext  
#!include auth-ldap.conf.ext  
!include auth-passwdfile.conf.ext  
#!include auth-checkpassword.conf.ext  
#!include auth-vpopmail.conf.ext  
#!include auth-static.conf.ext

## auth-passwdfile.conf.ext

**nano** auth-passwdfile.conf.ext

- # Authentication for passwd-file users. Included from 10-auth.conf.  
#  
# passwd-like file with specified location.  
# <doc/wiki/AuthDatabase.PasswdFile.txt>

```
passdb {
 driver = passwd-file
 args = scheme=SHA512-CRYPT username_format=%u /etc/dovecot/dovecot-users
}

userdb {
 driver = static
 args = uid=vmail gid=vmail home=/var/mail/vhosts/%d/%n
}
```

## Dovecot Users PasswdFile

```
doveadm pw -l
doveadm pw -s SHA512-CRYPT
nano ../dovecot-users
```

- #meinekleinefarm.net  
xenadmin@meinekleinefarm.net:{SHA512-CRYPT}\$6\$XYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyz
- #mgs-ullrich.de  
example@mgs-ullrich.de:{SHA512-CRYPT}\$6\$XYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyzXYZxyz

## 10-ssl.conf

```
nano 10-ssl.conf
```

- ssl = required  
ssl\_cert = </etc/letsencrypt/live/meinekleinefarm.net/fullchain.pem  
ssl\_key = </etc/letsencrypt/live/meinekleinefarm.net/privkey.pem

## 10-logging.conf

```
nano 10-logging.conf
```

- log\_path = /var/log/dovecot.log

## Setup logrotate

```
nano /etc/logrotate.d/dovecot
```

```
• /var/log/dovecot*.log {
 missingok
 notifempty
 delaycompress
 sharedscripts
 postrotate
 doveadm log reopen
 endscript
}
```

## Fin

```
systemctl restart dovecot
```

From:  
<https://dokuwiki.meinekleinefarm.net/> - **Meine kleine Dokumentation**

Permanent link:  
[https://dokuwiki.meinekleinefarm.net/doku.php?id=dovecot\\_installation&rev=1478725763](https://dokuwiki.meinekleinefarm.net/doku.php?id=dovecot_installation&rev=1478725763)

Last update: **2016/11/09 21:09**

