Piwik

Baustelle / Work in Progress

Quellen

- https://piwik.org/docs/installation/#the-5-minut-piwik-installation
- http://wordpress.org/extend/plugins/wp-piwik/
- https://www.dokuwiki.org/plugin:piwik2

```
cd /var/www/html/meinekleinefarm.net
wget https://builds.piwik.org/piwik.zip
unzip piwik.zip
rm piwik.zip
rm How\ to\ install\ Piwik.html
mysql -u root -p
```

```
CREATE USER 'piwik'@'localhost' IDENTIFIED BY 'PASSW0RD1';
CREATE DATABASE `piwik`;
GRANT ALL privileges ON `piwik`.* TO 'piwik'@'localhost';
flush privileges;
```

```
<VirtualHost *:80>
        ServerName piwik.meinekleinefarm.net
        Redirect permanent / https://piwik.meinekleinefarm.net/
</VirtualHost>

<IfModule mod_ssl.c>
        <VirtualHost *:443>
                ServerAdmin webmaster@meinekleinefarm.net
                ServerName piwik.meinekleinefarm.net
                ServerAlias piwik.meinekleinefarm.net

                DocumentRoot /var/www/html/meinekleinefarm.net/piwik/

                <Directory /var/www/html/meinekleinefarm.net/piwik/>
                        AllowOverride All
                </Directory>

                ErrorLog ${APACHE_LOG_DIR}/error.log
                CustomLog ${APACHE_LOG_DIR}/access.log combined

                SSLEngine on
                SSLCertificateFile
```

```
/etc/letsencrypt/live/meinekleinefarm.net/fullchain.pem
                SSLCertificateKeyFile
/etc/letsencrypt/live/meinekleinefarm.net/privkey.pem

                <FilesMatch "\.(cgi|shtml|phtml|php)$">
                                SSLOptions +StdEnvVars
                </FilesMatch>
                <Directory /usr/lib/cgi-bin>
                                SSLOptions +StdEnvVars
                </Directory>

                BrowserMatch "MSIE [2-6]" \
                                nokeepalive ssl-unclean-shutdown \
                                downgrade-1.0 force-response-1.0
                BrowserMatch "MSIE [17-9]" ssl-unclean-shutdown
        </VirtualHost>
</IfModule>
```

```
a2ensite piwik.meinekleinefarm.net.conf
service apache2 reload
```

Auf https://piwik.meinekleinefarm.net/ gehen um das 5-Minute Setup zu vervollständigen. Hier werden primär die MySQL Daten benötigt, es handelt sich um eine typisches Setup für eine Webapplikation.

CMS Plugins

https://piwik.org/integrate/

Wordpress

https://wordpress.org/plugins/wp-piwik/

Konfiguration über Angabe des API Auth Token, danach benötigte Optionen, sowie Tracking aktivieren.

Dokuwiki

https://www.dokuwiki.org/plugin:piwik2

From:
https://dokuwiki.meinekleinefarm.net/ - **Meine kleine Dokumentation**

Permanent link:
https://dokuwiki.meinekleinefarm.net/doku.php?id=piwik&rev=1480266288

Last update: **2016/11/27 17:04**